



**Energy**

National Research Programmes 70 and 71

# Project

## Self-regenerating catalysts





## Smart material for fuel cells regenerates itself

As low-CO<sub>2</sub>, efficient energy suppliers, high-temperature fuel cells for stationary use represent a promising technology for the future. However, the devices currently available are not yet robust enough and have an inadequate service life. A newly developed “smart” material promises to remedy this shortcoming.



In Japanese households, over 120,000 power units with fuel cells have been installed with government support. *Source:* AdobeStock





## At a glance

- An innovative material that regenerates itself makes stationary fuel cells more durable and thus more economical.
- Fuel cells equipped with the new material could be operated directly with CO<sub>2</sub>-neutral energy sources such as biogas.
- As efficient small-scale power plants that simultaneously supply buildings with electricity and heat, fuel cells could contribute to reducing CO<sub>2</sub> emissions.

An important aspect of Energy Strategy 2050 is an increasingly decentralised energy supply. Potential energy suppliers include stationary fuel cells, especially high-temperature fuel cells, which operate at temperatures of up to 900 degrees Celsius. In terms of efficiency, these small-scale power plants are unbeatable: a fuel cell can simultaneously supply a household with electricity and heat and at the same time harness 95 % of the energy in the fuel. In contrast, the current energy supply for households, which is fed by mains electricity and fossil energy sources, achieves an overall efficiency of just 60 %.

Thanks to their high efficiency, high-temperature fuel cells also emit less CO<sub>2</sub> than the energy suppliers commonly used today. CO<sub>2</sub> emissions can be reduced even further if CO<sub>2</sub>-neutral gas from renewable sources such as biomass is used as fuel.

Until now, however, fuel cells have not been able to establish themselves as an energy source. One problem is their relatively short service life, which makes the devices more expensive. Furthermore, high-temperature fuel cells are sensitive to sulphur compounds such as those found in biogas. Such impurities are therefore first removed from the gas – which is a costly process.

The Achilles' heel of the high-temperature fuel cell is the catalyst that splits the fuel molecules and thus releases hydrogen for the energy-generating reaction. Conventional catalysts do not tolerate repeated switching on and off very well because the catalytically active component nickel clumps and loses its function over time. The high operating temperature also has a similar damaging effect over time.



## Smart self-healing

This weakness is where the work of the researchers from the Zurich University of Applied Sciences (ZHAW) comes in. They have developed an innovative catalyst material with unique “smart” properties. The new material regenerates itself when the fuel is alternately switched on (reductive conditions) and off (oxidative conditions). Unlike conventional high-temperature fuel cells, this redox cycle is not harmful to the catalyst, but rather has a revitalising effect. Thanks to a newly developed manufacturing process, the nickel remains distributed in fine particles and thus retains its catalytic function over an extended period of time. Furthermore, the material not only works better with sulphur-containing fuels, but rather also performs at full capacity again after just two redox cycles. All of these advantages considerably extend the service life of the catalyst. The innovative material also has another attractive feature: compared to existing fuel cells, it reduces the nickel requirement by 90 % and thus promises to have a lower environmental impact.

## Well rooted

Unlike in the past, the nickel particles in the newly developed material do not lie on the carrier material, but are actually rooted in it. The researchers suspect that this stabilises the catalyst and prevents the nickel from clumping.

This is mainly due to a new manufacturing process. This ensures a highly pure and homogeneous mixing of the nickel with the other components and gives the material its “self-healing powers”. The researchers were able to show that these smart properties are also retained in a practical test setup.

## A promising start

There is still a long way to go, however, before the new catalyst material can be launched on the market, as it has not yet been installed in any fuel cell. Other material properties also play a role in the performance of the complete device – especially electrical conductivity. This is currently much lower than that of conventional catalysts. A fuel cell with the new material in its currently available form would therefore still deliver insufficient power.



## Market measures are also required

However, the scientists also point to the market situation, which is currently unfavourable for the spread of fuel cell systems. In Switzerland, for example, there is no nationwide promotion of such devices, and the low electricity prices reduces their cost-effectiveness. Furthermore, consumers are not yet aware enough of the technology and its advantages.



**Energy**

National Research Programmes 70 and 71

## Produkte aus diesem Projekt



- Fundamental relationships between 3D pore topology, electrolyte conduction and flow properties: Towards knowledge-based design of ceramic diaphragms for sensor applications  
Date of publication: 01.01.18
- Structural Reversibility and Nickel Particle stability in Lanthanum Iron Nickel Perovskite-Type Catalysts  
Date of publication: 01.01.18
- Big Data for Microstructure-Property Relationships: A Case Study of Predicting Effective Conductivities  
Date of publication: 01.01.18
- Lanthanum doped strontium titanate - ceria anodes: Deconvolution of impedance spectra and relationship with composition and microstructure  
Date of publication: 01.01.18
- Smart material concept: reversible microstructural self-regeneration for catalytic applications  
Date of publication: 01.01.18
- Microstructure-property relationships in a gas diffusion layer (GDL) for Polymer Electrolyte Fuel Cells  
Date of publication: 01.01.18
- Stochastic 3D modeling of complex three-phase microstructures in SOFC-electrodes with completely connected phases  
Date of publication: 01.01.18
- SMART catalyst based on doped Sr-titanite for advanced SOFC anodes  
Date of publication: 01.01.18
- Optimization of Ni-YSZ Anode Performance by Virtual Materials Testing  
Date of publication: 01.01.18
- Exsolution and integration of nanosized SMART catalysts for next generation SOFC anodes  
Date of publication: 01.01.18
- LST-CGO anodes: deconvolution of impedance spectra and relationship with composition and microstructure  
Date of publication: 01.01.18
- Lanthanum doped strontium titanate - ceria anodes: Deconvolution of impedance spectra and relationship with composition and microstructure  
Date of publication: 01.01.18
- SMART catalyst based on doped Sr-titanite for advanced SOFC anodes  
Date of publication: 01.01.18
- Exsolution and integration of nanosized SMART catalysts for next generation SOFC anodes  
Date of publication: 01.01.18
- Self Self-regenerating catalyst for efficient energz production with renewable fuels  
Date of publication: 01.01.18
- Renewable fuels for sustainable electricity production  
Date of publication: 01.01.18
- Puzzleteile eines neuen Energiesystems  
Date of publication: 01.01.18



**Energy**

National Research Programmes 70 and 71

## Contact & Team

Prof. Dr. André Heel  
HSR Hochschule für Technik Rapperswil  
Oberseestrasse 10  
Rapperswil  
+41 (0)55 222 41 11



Andre Heel  
Projektleitung



Dariusz Burnat



Lorenz Holzer

All information provided on these pages corresponds to the status of knowledge as of 17.12.2018.